

Properties	Technology	Fused Filament Fabrication	
Print head	Dual extruder with one nozzle (3 nozzle diameters included)		
	Build volume XYZ mm	Builder Extreme 3000 PRO – 1100x1100x820	
	Layer resolution	0.4 mm nozzle – 0.1 - 0.3 mm	
		0.8 mm nozzle – 0.2 - 0.7 mm	
		1.2 mm nozzle – 0.3 - 0.9 mm	
	Print speed	up to 300 mm p/s (standard speed 80 mm p/s)	
	Build plate	Heated aluminium plate up to 60 degrees	
	Nozzle diameter	0.4 mm standard. 0.8 and 1.2 are included	
	Operating sound	<30 db	
	Operating temp	15 – 25 degrees Celsius	
	Connectivity	USB, Wi-Fi, LAN	
Physical dimensions	Dimensions	MM	Builder Extreme 3000 PRO – 1500x1380x1550
Shipping dimensions	Dimensions	CM	Builder Extreme 3000 PRO – soon available
Weight			Builder Extreme 3000 PRO – 285 kg
Electrical requirements			
	Power	1800 watts (at peak)	
Software	Supplied software	Simplify3D	
	Supported	MAC, Windows	
Warranty	Warranty period	Builder Extreme PRO – 12 months	
		Print head – 3 months	